

# Cityline Grid都市网络

ANKER



## 产品技术参数

|      |                                 |
|------|---------------------------------|
| 结构   | 簇绒高低圈                           |
| 标准纤维 | 100% Polyamid SD                |
| 染色方式 | 100% 原液染纱                       |
| 底背   | Unit Back® (PVC & Bitumen Free) |

|      | 英制                    | 公制                   |
|------|-----------------------|----------------------|
| 绒高   | 0.17 in               | 4.5mm±0.5mm          |
| 产品尺寸 | 19.69 in X 19.69      | 50cm X 50cm          |
| 针密   | 12 in                 | 47 / 10cm            |
| 针距   | 1/12 in               | 47.2 / 10cm          |
| 绒重   | 18 oz/yd <sup>2</sup> | 610 g/m <sup>2</sup> |
| 总厚度  | 0.24 in               | 6±0.5mm              |

## 功能特性

|       |           |             |
|-------|-----------|-------------|
| 耐磨等级  | 33-LC1    |             |
| 六足滚轮  | ISO 10361 | 12000 转≥3.5 |
| 人流量等级 | 重度商业使用空间  |             |

## 性能指标

|         |                |                 |
|---------|----------------|-----------------|
| 隔音性     | ISO 10140      | ca. 23dB        |
| 吸音性     | ISO 354        | $\alpha_w=0.25$ |
| 热阻性     | ISO 8302       | ca. 0.07        |
| 阻燃性     | DIN EN 13501-1 | Cfl-s1          |
| 抗静电     | ISO 6356       | ≤2.0 kV         |
| 耐光色牢度   | ISO 105 B02    | ≥6              |
| 耐水色牢度   | ISO 105 E01    | ≥4              |
| 干湿摩擦色牢度 | ISO 105 X12    | ≥3-4            |
| 稳定性拔出力  | ISO 4919       | ≥30N            |

## 环保认证

|               |                           |
|---------------|---------------------------|
| GUT           | TVOC≤100µg/m <sup>3</sup> |
| Declare Label |                           |
| EPD           |                           |

## 质保

15年耐磨有限保证  
终身抗静电有限保证  
终身抗褪色有限保证

## 证书



Declare.



## 铺装方式



顺拼