

Mobile Dune 沙海

ANKER



产品技术参数

结构	簇绒高低圈	
标准纤维	100% Econyl Regenerated Nylon	
染色方式	100% 溶液染纱	
底背	Unit Back® (PVC & Bitumen Free)	
绒高 产品尺寸 针密 针距 绒重 总厚度	英制	公制
	0.17 in	4.5mm±0.5mm
	18 in X 36 in	45.72 cm X 91.44 cm
	11 in	42 / 10cm
	1/10 in	39 / 10cm
	24 oz/yd ²	813 g/m ²
	0.26 in	6.5±0.5mm

功能特性

耐磨等级	33-LC1	
六足滚轮	ISO 10361	12000 转≥3.5
人流量等级	重度商业使用空间	

性能指标

隔音性	ISO 10140	ca. 23dB
吸音性	ISO 354	$\alpha_w=0.25$
热阻性	ISO 8302	ca. 0.07
阻燃性	DIN EN 13501-1	Cfl-s1
抗静电	ISO 6356	≤2.0 kV
耐光色牢度	ISO 105 B02	≥6
耐水色牢度	ISO 105 E01	≥4
干湿摩擦色牢度	ISO 105 X12	≥3-4
稳定性拔出力	ISO 4919	≥30N

环保认证

GUT	TVOC≤100μg/m ³
Declare Label	
EPD	


质保

15年耐磨有限保证
终身抗静电有限保证
终身抗褪色有限保证


证书



Declare.



铺装方式



竖砖拼