

# On Mars 秘境

ANKER



## 产品技术参数

|                                     |                                             |                      |
|-------------------------------------|---------------------------------------------|----------------------|
| 结构                                  | 簇绒高低圈                                       |                      |
| 标准纤维                                | 100% Aquafil Nylon                          |                      |
| 染色方式                                | 100% 原液染纱                                   |                      |
| 底背                                  | Unit Back <sup>®</sup> (PVC & Bitumen Free) |                      |
| 绒高<br>产品尺寸<br>针密<br>针距<br>绒重<br>总厚度 | 英制                                          | 公制                   |
|                                     | 0.17 in                                     | 4.5mm±0.5mm          |
|                                     | 18 in X 36 in                               | 45.72 cm X 91.44 cm  |
|                                     | 11 in                                       | 41/ 10cm             |
|                                     | 1/10 in                                     | 39 / 10cm            |
|                                     | 21 oz/yd <sup>2</sup>                       | 712 g/m <sup>2</sup> |
|                                     | 0.26 in                                     | 6.5±0.5mm            |

## 功能特性

|       |           |             |
|-------|-----------|-------------|
| 耐磨等级  | 33-LC1    |             |
| 六足滚轮  | ISO 10361 | 12000 转≥3.5 |
| 人流量等级 | 重度商业使用空间  |             |

|         |                |                 |
|---------|----------------|-----------------|
| 隔音性     | ISO 10140      | ca. 23dB        |
| 吸音性     | ISO 354        | $\alpha_w=0.25$ |
| 热阻性     | ISO 8302       | ca. 0.07        |
| 阻燃性     | DIN EN 13501-1 | Cfl-s1          |
| 抗静电     | ISO 6356       | ≤2.0 kV         |
| 耐光色牢度   | ISO 105 B02    | ≥6              |
| 耐水色牢度   | ISO 105 E01    | ≥4              |
| 干湿摩擦色牢度 | ISO 105 X12    | ≥3-4            |
| 稳定性拔出力  | ISO 4919       | ≥30N            |

## 环保认证

|               |                           |
|---------------|---------------------------|
| GUT           | TVOC≤100μg/m <sup>3</sup> |
| Declare Label |                           |
| EPD           |                           |

## 质保

15年耐磨有限保证  
终身抗静电有限保证  
终身抗褪色有限保证


## 证书



Declare.



## 铺装方式



竖砖拼